Printing date 02/04/2016 Revised On 01/15/2016

1 Identification of the substance and manufacturer

Trade name: **COLD GALV** 0000161445 **Product code:**

Product category PC9a Paints and coatings. Seymour of Sycamore Manufacturer/Supplier: 917 Crosby Avenue Sycamore, IL 60178 Phone: 815-895-9101 www.seymourpaint.com

Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Skin Irrit. 2 H315 Causes skin irritation.

Repr. 1B H360 May damage fertility or the unborn child. STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

GHS02 GHS04 GHS07 GHS08

Signal word Danger

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Causes skin irritation.

May damage fertility or the unborn child. May cause drowsiness or dizziness.

May cause damage to organs through prolonged or repeated exposure.

Precautionary statements Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use.

Wash hards thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves.
Do not breathe dust/fume/gas/mist/vapors/spray.
IF INHALED: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER/doctor if you feel unwell.

If skin irritation occurs: Get medical advice/attention. IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse.

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Protect from sunlight. Store in a well-ventilated place.

Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures

Chemical Description: This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous	components:	
	zinc powder	44.98%
108-88-3		24.34%
74-98-6	propane	12.6%
106-97-8		7.4%
64742-47-8	Mineral Spirits	3.46%
	isopropyl alcohol	2.28%
872-50-4	N-methyl-2-pyrrolidone	0.15%

4 First-aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Remove contaminated clothing. Wash exposed area with soap and water.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a After eve contact:

doctor.

After swallowing: Rinse out mouth and then drink plenty of water. Rinse mouth with water. Do not induce vomiting.

Most important symptoms and

effects:

Indication of any immediate medical

attention needed: No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: CO2, extinguishing powder or water spray. Fight larger fires with water spray.

(Contd. on page 2)

(Contd. of page 1)

Safety Data Sheet

Printing date 02/04/2016 Revised On 01/15/2016

Trade name: COLD GALV

firefighters:

Special hazards: Protective equipment for Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away. Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling Storage requirements:

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8 Exposure controls/personal protection

Components wit	th limit values	s that re	quire mon	nitoring at	the work	place:

108-88-3 Toluene PEL (USA)

Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift

Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm REL (USA)

TLV (USA) Long-term value: 75 mg/m³, 20 ppm

74-98-6 propane

PEL (USA) Long-term value: 1800 mg/m³, 1000 ppm

Long-term value: 1800 mg/m³, 1000 ppm REL (USA) TLV (USA) refer to Appendix F inTLVs and BEIs book

106-97-8 n-butane

REL (USA) Long-term value: 1900 mg/m³, 800 ppm

TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

67-63-0 isopropyl alcohol

PEL (USA) Long-term value: 980 mg/m³, 400 ppm

Short-term value: 1225 mg/m³, 500 ppm REL (USA) Long-term value: 980 mg/m³, 400 ppm

Short-term value: 984 mg/m³, 400 ppm Long-term value: 492 mg/m³, 200 ppm TLV (USA)

BEI

872-50-4 N-methyl-2-pyrrolidone

WEEL (USA) Long-term value: 10 ppm

Ingredients with biological limit values:

108-88-3 Toluene

BEI (USA) 0.02 mg/L Medium: blood

Time: prior to last shift of workweek Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine

Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

67-63-0 isopropyl alcohol

BEI (USA) 40 mg/L

Medium: urine

Time: end of shift at end of workweek

Parameter: Acetone (background, nonspecific)

872-50-4 N-methyl-2-pyrrolidone

BEI (USA) 100 mg/L

Medium: urine Time: end of shift

Parameter: 5-Hydroxy-N-methyl-2-pyrrolidone

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

(Contd. on page 3)

(Contd. of page 2)

Printing date 02/04/2016 Revised On 01/15/2016

Trade name: COLD GALV

Eye protection:

Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment: A respirator is generally not necessary when using this product outdoors or in large open areas.

In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine.

Hand protection:

Nyshid:
Nitrile gloves.
Protective gloves. The glove material must be impermeable and resistant to the substance.
Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic Odor threshold: Not determined. pH-value: Not determined Melting point/Melting range Undetermined. **Boiling point:** -44 °C (-47 °F) Flash point: -19 °C (-2 °F)

Flammability (solid, gas): Extremely flammable. **Decomposition temperature:** Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

Lower Explosion Limit: 1.7 Vol % 10.9 Vol % **Upper Explosion Limit:** Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapour density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined. VOC content: VOC content (less exempt solvents): 570.0 g/l / 4.76 lb/gl

50.2 % MIR Value: 1.20 Solids content: 49.8 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures.

Chemical stability: Not fully evaluated.

Possibility of hazardous reactions: No dangerous reactions known. Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 v	LD/LC50 values that are relevant for classification:			
	106-97-8 n-butane			
Inhalative	Inhalative LC50/4 h 658 mg/l (rat)			
67-63-0 is	67-63-0 isopropyl alcohol			
Oral	LD50	4570 mg/kg (rat)		
Dermal	LD50	13400 mg/kg (rab)		
Inhalative	LC50/4 h	30 mg/l (rat)		
872-50-4 N	872-50-4 N-methyl-2-pyrrolidone			
Oral	LD50	3600 mg/kg (rat)		
Dermal	LD50	8000 mg/kg (rbt)		
	Information on tentral plants that a No. 1 (1991)			

Information on toxicological effects: No data available.

Skin effects: Irritant to skin and mucous membranes.

Eye effects: Irritating effect.

No sensitizing effects known. Sensitization:

Carcinogenic categories

IARC (Int	ernational	Agency for	Research (on Cancer)

 <u> </u>				_
108-88-3	Toluene			,
67-63-0	isopropyl alco	hol		(

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability: The product is degradable after prolonged exposure to natural weathering processes.

(Contd. on page 4)

3 3 Printing date 02/04/2016 Revised On 01/15/2016

Trade name: COLD GALV

No further relevant information available.

(Contd. of page 3)

Bioaccumulative potential: Mobility in soil: No further relevant information available. Other adverse effects: No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Completely empty cans should be recycled. Recommendation:

14 Transport information

UN-Number UN1950 DOT N/A UN1950

DOT Consumer Commodity ORM-D

Aerosols, flammable 1950 Aerosols, ENVIRONMENTALLY HAZARDOUS ADR

Transport hazard class(es):

Class 2.1 Marine pollutant: Yes

Symbol (fish and tree) Special marking (ADR): Symbol (fish and tree) Special precautions for user: Warning: Gases

EMS Number: F-D,S-Ŭ

Quantity limitations On passenger aircraft/rail: 75 kg On cargo aircraft only: 150 kg

ADR

IMDG

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

Limited quantities (LQ) 1L

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

Packaging Group: UN "Model Regulation": UN1950, Aerosols, ENVIRONMENTALLY HAZARDOUS, 2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

7440-66-6 zinc powder 108-88-3 Toluene

67-63-0 isopropyl alcohol

1314-13-2 zinc oxide

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead. CPSC:

California Proposition 65 chemicals known to cause cancer:

None of the ingredients in this product are listed

California Proposition 65 chemicals known to cause developmental

toxicity:

108-88-3 Toluene 872-50-4 N-methyl- pyrrolidone

CANADIAN ENVIRONMENTAL

PROTECTION ACT:

All hazardous ingredients for this product appear on the Canadian Domestice Substance List. A - Compressed gas
D2A - Very toxic material causing other toxic effects WHMIS Symbols for Canada:



	EPA:	
	7440-66-6 zinc powder	D, I, II
	108-88-3 Toluene	II
ı	1314-13-2 zinc oxide	D, I, II

16 Other information

Contact: Regulatory Affairs Date of preparation / last revision 02/04/2016 / -