




Atlanta, Georgia

Phone 800-521-7326

Fax 770-745-1333

Drop In Anchors (CY) (Zinc & Stainless)



Drop In Anchors are a two piece, internally threaded expansion anchor. The anchor is for flush mounting, medium to heavy duty applications in solid base materials such as stone or concrete.

Zinc Part	304 SS Part	Anchor Size Bolt Size	Hole Diameter	Minimum Embedment	Allowable Load Capacity	
					2000 PSI Concrete	
					Tensile (lbs.)	Shear (lbs.)
CY9220	6325SS	1/4-20	3/8	1"	255	230
CY9230	6337SS	3/8-16	1/2	1-1/2"	717	790
CY9240	6350SS	1/2-13	5/8	2"	1157	1170
CY9250	6362SS	5/8-11	7/8	2-1/2"	1255	
CY9260	6375SS	3/4-10	1"	3-1/8"	1560	

Allowable load capacities listed are calculated using an applied safety factor of 4.

Peco Fasteners specification sheets are a reference guide to help in the selection of fasteners. Peco has made every effort to ensure the accuracy of the information. However, Peco Fasteners is not responsible for any errors that may be contained within these sheets. Peco Fasteners makes no claim of warranty in the accuracy of this information. Users of this information are solely responsible for protecting themselves against liability. It is solely the responsibility of the purchasers and users of these fasteners to consult with Engineers that are experts in an applicable field. Peco Fasteners is not responsible for any loss, claim, or damage due to these specification sheets.