

Phone 800-521-7326

Ring Terminals Nylon Insulated

- w	-	12	
1 - Inw	+,	12	
1 2	1		
- <u>m</u>	- 0.1	D.	
1cm	8		

'A!A	ġ.,	18	1	같.	1	1
	1	1	1			ł
the second second second)	-f	1		L.F	t.

Terminal Type	Catalog Number	UPC	Insulator	UL Listed	CSA Listed	Wire Size	Stud Width	0.D.	Insulator I.D	Uninsulated Length (L)	Insulated Length (L)	w	ıw	F		
RINGS	C50020N	705591812642	Nylon	Yes	Yes	22-18	6	.133		.66	0.87	.290	.138/.142	.260		
RINGS	C50030N	705591812659	Nylon	Yes	Yes	22-18	8	/.13	/.13 min165 5	.66	0.88	.324	.168/.171	.250		
RINGS	C50040N	705591812666	Nylon	Yes	Yes	22-18	10	5		.66	0.88	.324	.194/.197	.250		
RINGS	C50086N	705591812703	Nylon	Yes	Yes	16-14	6	.152		0.66	0.88	.295	.138/.14	.260		
RINGS	C50090N	705591812710	Nylon	Yes	Yes	16-14	8	-	.15 min185 6	0.71	0.93	.324	.108/.17	.295		
RINGS	C50100N	705591812727	Nylon	Yes	Yes	16-14	10			0.71	0.93	.324	.194/.19	.295		
RINGS	C50101N	705591812734	Nylon	Yes	Yes	16-14	1/4	U		.89	1.11	.470	.263/.26	.405		
RINGS	C50220N	705591812772	Nylon	Yes	Yes	12-10	8	.217 /.22 0				.72	1.02	.342	.108/.17	.297
RINGS	C50230N	705591812789	Nylon	Yes	Yes	12-10	10			.72	1.02	.342		.297		
RINGS	C50240N	705591812796	Nylon	Yes	Yes	12-10	1/4		min235	.99	1.30	.558	.2577.20	.469		
RINGS	C50250N	705591812802	Nylon	Yes	Yes	12-10	5/16			.99	1.30	.558		.469		
RINGS	C50260N	705591812819	Nylon	Yes	Yes	12-10	3/8			.99	1.30	.558	.394/.39	.469		

Material Thickness : 22-18 = .028, 16-14= .030, 12-10= .038 All Barrel Lengths: .250

Peco Fasteners specification sheets are a reference guide to help in the selection of fasteners. Peco has made every effort to ensure the accuracy of the information. However, Peco Fasteners is not recorrection of specification is need and a relative glade to may in the specification of instants as performed in the specification of instants are expensible for any loss, claim, or damage due to these specification sheets.

7/29/2015