



PRODUCT TECHNICAL DATA SHEET



MOLY PTFE LUBRICANT ICA391

FOR INDUSTRIAL USE

DESCRIPTION: Formulated with PTFE and fortified with Moly to provide long lasting lubrication and protection from friction, wear and corrosion. Fast acting; temperature resistant to 500°F, its light viscosity allows for deep penetration into hard to reach moving parts. Displaces moisture. Safe to use on most surfaces. Ideal for extreme conditions, penetrates and protects metal against rust and corrosion.

FEATURES:

- Heat Stable to 500°F
- Displaces Moisture
- Protects Metal
- Penetrates
- PTFE, Moly Based
- Fast acting

Specs:

Can Size	20 oz
Net Weight	15 oz
Shipping Weight	15 lbs
Packaged	12 cans per case
Product Number	ICA391

Regulatory:

Recyclable Package	Yes
VOC Compliant CARB/OTC	CARB Compliant by use of the Alternative Compliance Method
Flammability	Flammable
24 Hour Medical Emergency	1-866-836-8855

Physical Characteristics:

Color	Gray / Black
Fragrance	Pine
Shelf Life	1 year +



Distributed by:
Peco Fastener | 1218-A Six Flags Road
Austell, GA 30336 | 770-745-1300

