



Atlanta, Georgia

Phone 800-521-7326

Fax 770-745-1333

Winged Wire Connectors

UL Listed/RoHS Compliant

Temperature Rating - 105 Degrees Celsius (221 Degrees F)

Flame Retardant UL 94V-2 Thermoplastic Shell

Pre-Twisting Of Wire Is Not Necessary

Color	Catalog Number	UPC	Wire Range	Max Voltage	UL Listed	Minimum Wire Range	Maximum Wire Range	Wire Type
Yellow	POY1	705591810860	18-10 AWG	600V	UL 486C	2 #18 AWG	3 #12 AWG	Copper Only
Yellow	PBPOY1	705591812086	18-10 AWG	600V	UL 486C	2 #18 AWG	3 #12 AWG	Copper Only
Tan	POT4	705591810877	22-8 AWG	600V	UL 486C	3 #20 AWG	4 #12 AWG	Copper Only
Tan	PBPOT4	705591812093	22-8 AWG	600V	UL 486C	3 #20 AWG	4 #12 AWG	Copper Only
Red	POR2	705591810884	18-8 AWG	600V	UL 486C	3 #16 AWG	5 #12 AWG	Copper Only
Red	PBPOR2	705591812109	18-8 AWG	600V	UL 486C	3 #16 AWG	5 #12 AWG	Copper Only
Blue	POB3	705591810907	14-6 AWG	600V	UL 486C	2 #10 w/1 #12 AWG	1 #8 w/3 #10 AWG	Copper Only
Blue	PBPOB3	705591810921	14-6 AWG	600V	UL 486C	2 #10 w/1 #12 AWG	1 #8 w/3 #10 AWG	Copper Only

Peco Fasteners specification sheets are a reference guide to help in the selection of fasteners. Peco has made every effort to ensure the accuracy of the information. However, Peco Fasteners is not responsible for any errors that may be contained within these sheets. Peco Fasteners makes no claim of warranty in the accuracy of this information. Users of this information are solely responsible for protecting themselves against liability. It is solely the responsibility of the purchasers and users of these fasteners to consult with Engineers that are experts in an applicable field. Peco Fasteners is not responsible for any loss, claim, or damage due to these specification sheets.