



Atlanta, Georgia

Phone 800-521-7326

Fax 770-745-1333

Composite Double Braid Rope With Pulling Eyes



Peco Catalog#	Diameter (in.)	Length (ft.)	Minimum Break Strength (lbs.)	Approximate Density (lbs./100ft.)	Circumference Inches
Special Order	1/4	600	1,550	2	3/4
Special Order	1/4	1200	1,550	2	3/4
PR38X600	3/8	600	5,000	4.5	1-1/8
Special Order	3/8	1200	5,000	4.5	1-1/8
Special Order	7/16	600	7,500	6.1	1-1/4
Special Order	7/16	1200	7,500	6.1	1-1/4
PR12X600	1/2	600	9,500	8.1	1-1/2
PR12X1200	1/2	1200	9,500	8.1	1-1/2
Special Order	9/16	600	16,150	10	1-3/4
Special Order	9/16	1200	16,150	10	1-3/4
Special Order	5/8	600	18,000	13	2
Special Order	5/8	1200	18,000	13	2
PR34X600	3/4	600	26,000	18	2-1/4
Special Order	3/4	1200	26,000	18	2-1/4
PR78X600	7/8	600	32,000	25	2-3/4
PR78X1200	7/8	1200	32,000	25	2-3/4
Special Order	1	600	42,000	32	3
Special Order	1	1200	42,000	32	3

High Strength, Low Stretch. Resistance to UV Rays, Chemicals, & Abrasion. Factory spliced pulling eye on each end.