Printing date 01/25/2016 Revised On 01/25/2016

1 Identification of the substance and manufacturer

Trade name: **GREEN**

0000100008 Product code:

PC9a Paints and coatings. **Product category** Seymour of Sycamore Manufacturer/Supplier: 917 Crosby Avenue Sycamore, IL 60178 Phone: 815-895-9101 www.seymourpaint.com

Emergency telephone number: CHEMTEL 1-800-255-3924, or 813-248-0585.

2 Hazard(s) identification

Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.

STOT SE 3 H336 May cause drowsiness or dizziness.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

GHS Hazard pictograms

Precautionary statements

GHS02 GHS04 GHS07 GHS08

Signal word

Hazard statements Extremely flammable aerosol.

Contains gas under pressure; may explode if heated. Causes skin irritation.

Causes serious eye irritation.

Suspected of damaging fertility or the unborn child.

May cause drowsiness or dizziness

May cause damage to organs through prolonged or repeated exposure.

Obtain special instructions before use.

Keep away from heat/sparks/open flames/hot surfaces. No smoking.

Do not spray on an open flame or other ignition source.

Do not pierce or burn, even after use. Wash hands thoroughly after handling. Use only outdoors or in a well-ventilated area.

Wear protective gloves/protective clothing/eye protection/face protection.

Do not handle until all safety precautions have been read and understood.

Wear protective gloves.
Do not breathe dust/fume/gas/mist/vapors/spray.

Do not breatne dustrume/gas/mist/vapors/spray.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Call a POISON CENTER/doctor if you feel unwell.

If skin irritation occurs: Get medical advice/attention.

IF ON SKIN: Wash with plenty of water.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Store locked up

Store locked up.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

Protect from sunlight. Store in a well-ventilated place. Store in a well-ventilated place. Keep container tightly closed.

Dispose of contents/container in accordance with local/regional/national/international

regulations.

3 Composition/information on ingredients

Chemical characterization: Mixtures Chemical Description:

This product is a mixture of the substances listed below with nonhazardous additions.

Dangerous components:			
74-98-6	propane	22.04%	
	Acetone	21.18%	
108-88-3		17.8%	
	n-butane	12.94%	
142-82-5		10.97%	
	VM&P Naphtha	1.5%	
108-65-6	PM acetate	1.03%	

4 First-aid measures

After swallowing:

After inhalation: Supply fresh air; consult doctor in case of complaints. After skin contact:

Immediately wash with water and soap and rinse thoroughly.
Remove contaminated clothing. Wash exposed area with soap and water.
Rinse opened eye for several minutes under running water. If symptoms persist, consult a After eye contact:

doctor. Rinse out mouth and then drink plenty of water.

Rinse mouth with water. Do not induce vomiting.

(Contd. on page 2)

(Contd. of page 1)

Printing date 01/25/2016 Revised On 01/25/2016

Trade name: GREEN

Most important symptoms and

effects:

Dizziness

Indication of any immediate medical attention needed:

No further relevant information available.

5 Fire-fighting measures

Extinguishing agents: Special hazards:

Protective equipment for

firefighters:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Can form explosive gas-air mixtures.

A respiratory protective device may be necessary.

6 Accidental release measures

Personal precautions, protective equipment and emergency

procedures:

Wear protective equipment. Keep unprotected persons away.

Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and material for containment and cleaning up:

Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

7 Handling and storage

Precautions for safe handling

Use only in well ventilated areas.

Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up. Storage requirements:

8 Exposure controls/personal protection

Components with lim	it values that require monitoring at the workplace:
74-98-6 propane	

PEL (USA)

Long-term value: 1800 mg/m³, 1000 ppm REL (USA) Long-term value: 1800 mg/m³, 1000 ppm refer to Appendix F inTLVs and BEIs book TLV (USA)

67-64-1 Acetone

Long-term value: 2400 mg/m³, 1000 ppm PEL (USA) REL (USA) Long-term value: 590 mg/m³, 250 ppm

Short-term value: 1187 mg/m³, 500 ppm Long-term value: 594 mg/m³, 250 ppm TLV (USA)

108-88-3 Toluene

PEL (USA)

Long-term value: 200 ppm Ceiling limit value: 300; 500* ppm *10-min peak per 8-hr shift

Short-term value: 560 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm REL (USA)

TLV (USA)

Long-term value: 75 mg/m³, 20 ppm BEI

106-97-8 n-butane

Long-term value: 1900 mg/m³, 800 ppm REL (USA)

TLV (USA) Short-term value: 2370 mg/m³, 1000 ppm

142-82-5 heptane

PEL (USA) Long-term value: 2000 mg/m³, 500 ppm

REL (USA)

Long-term value: 350 mg/m³, 85 ppm Ceiling limit value: 1800* mg/m³, 440* ppm *15-min

Short-term value: 2050 mg/m³, 500 ppm Long-term value: 1640 mg/m³, 400 ppm TLV (USA)

108-65-6 PM acetate

WEEL (USA) Long-term value: 50 ppm

Ingredients with biological limit values:

67-64-1 Acetone

BEI (USA) 50 mg/L

Medium: urine Time: end of shift

Parameter: Acetone (nonspecific)

(Contd. on page 3)

(Contd. of page 2)

Printing date 01/25/2016 Revised On 01/25/2016

Trade name: GREEN

108-88-3 Toluene

BEI (USA) 0.02 mg/L

Medium: blood

Time: prior to last shift of workweek

Parameter: Toluene

0.03 mg/L Medium: urine Time: end of shift Parameter: Toluene 0.3 mg/g creatinine Medium: urine Time: end of shift

Parameter: o-Cresol with hydrolysis (background)

Hygienic protection: Keep away from foodstuffs and animal feed. Wash hands after use.

Immediately remove all soiled and contaminated clothing.

Wash hands after use.

Avoid contact with the eyes and skin. Do not eat or drink while working.

Breathing equipment:

A respirator is generally not necessary when using this product outdoors or in large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical

hygeine. Nitrile gloves.

Hand protection:

Protective gloves. The glove material must be impermeable and resistant to the substance.

Eye protection: Tightly sealed goggles

9 Physical and chemical properties

Appearance: Aerosol. Odor: Aromatic **Odor threshold:** Not determined. pH-value: Not determined. Melting point/Melting range Undetermined. **Boiling point:** -44 °C (-47 °F) Flash point: -19 °C (-2 °F) Flammability (solid, gas): Extremèly flammable.

Decomposition temperature: Not determined.

Auto igniting: Product is not self-igniting.

Danger of explosion: In use, may form flammable/explosive vapour-air mixture. 1.1 Vol %

Lower Explosion Limit: **Upper Explosion Limit:** 10.9 Vol % Vapor pressure: Not determined.

Relative Density: Between 0.77 and 0.85 (Water equals 1.00)

Vapour density Not determined. **Evaporation rate** Not applicable. Partition coefficient: n-octonal/water: Not determined. Solubility: Not determined. Viscosity: Not determined. 575.7 g/l / 4.80 lb/gl

VOC content: VOC content (less exempt solvents): 67.0 % MIR Value: 1.19

Solids content: 11.8 %

10 Stability and reactivity

Reactivity: Stable at normal temperatures.

Conditions to avoid: Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing

temperatures. Not fully evaluated.

Chemical stability: Possibility of hazardous reactions: No dangerous reactions known.

Incompatible materials: No further relevant information available. Hazardous decomposition: No dangerous decomposition products known.

11 Toxicological information

LD/LC50 values that are relevant for classification:

106-97-8 n-butane

Inhalative LC50/4 h 658 mg/l (rat)

108-65-6 PM acetate

Oral LD50 8500 mg/kg (rat) Inhalative LC50/4 h 35.7 mg/l (rat)

Information on toxicological effects: No data available.

Skin effects: Irritant to skin and mucous membranes.

Eye effects: Irritating effect.

(Contd. on page 4)

3

(Contd. of page 3)

Printing date 01/25/2016 Revised On 01/25/2016

Trade name: GREEN

Sensitization: No sensitizing effects known.

Carcinogenic categories

IARC (International Agency for Research on Cancer)

108-88-3 Toluene

NTP (National Toxicology Program)

None of the ingredients is listed.

12 Ecological information

Aquatic toxicity: Hazardous for water, do not empty into drains.

Persistence and degradability:

The product is degradable after prolonged exposure to natural weathering processes. No further relevant information available.

Bioaccumulative potential: Mobility in soil:

No further relevant information available.

Ecotoxical effects:

Remark:

Toxic for fish

Other adverse effects:

No further relevant information available.

13 Disposal considerations

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Recommendation: Completely empty cans should be recycled.

14 Transport information

 UN-Number
 UN1950

 DOT
 N/A

 UN1950

DOT Consumer Commodity ORM-D

Aerosols, flammable 1950 Aerosols,

ADR Transport hazard class(es):

Class

Class 2.1 Marine pollutant: Yes

Marine pollutant: Yes Symbol (fish and tree)

Special marking (ADR): Symbol (fish and tree)
Special precautions for user: Warning: Gases

EMS Number:

F-D,S-Ŭ

Quantity limitations

On passenger aircraft/rail: 75 kg
On cargo aircraft only: 150 kg

ADR

Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

IMDG

Limited quantities (LQ) 1L Excepted quantities (EQ) 1L Code: E0

Not permitted as Excepted Quantity

Packaging Group: UN "Model Regulation":

UN "Model Regulation": UN1950, Aerosols,2.1

15 Regulatory information

SARA Section 355 (extremely hazardous substances):

None of the ingredients in this product are listed.

SARA Section 313 (Specific toxic chemical listings):

108-88-3 Toluene

CPSC: This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

California Proposition 65 chemicals known to cause cancer:

100-41-4 ethyl benzene 1333-86-4 Carbon black

California Proposition 65 chemicals

known to cause developmental

toxicity:

108-88-3 Toluene

CANADIAN ENVIRONMENTAL

PROTECTION ACT:

WHMIS Symbols for Canada:

All hazardous ingredients for this product appear on the Canadian Domestice Substance List.

A - Compressed gas

D2A - Very toxic material causing other toxic effects



EPA:		
67-64-1	Acetone	I
108-88-3	Toluene	Ш
	(Contd. on p.	120e 5)

Page 5/5

Safety Data Sheet

Printing date 01/25/2016 Revised On 01/25/2016

Trade name: GREEN

142-82-5 heptane

(Contd. of page 4)

16 Other information

Contact: Date of preparation / last revision

Regulatory Affairs 01/25/2016 / -